

EASO STEREO CO., LTD.

E-mail: audiopro@ms10.hinet.net
easoco@ms17.hinet.net

4F, No.951, Chung-Cheng Rd., Chung-Ho City.

Taipei. 235 Taiwan. R.O.C.

Tel: 886-2-8228 1100 Fax: 886-2-8228 6101

5 BAND STEREO EQUALIZER PRE-AMP High Performance Pre-Amp EMQ-6



MODEL NO.: EMQ-6

OEM and ODM orders are welcome

- 5 BANDS STEREO EQUALIZER 45Hz, 100Hz, 700Hz, 2KHz, 15KHz,
- 5 BANDS EQUALIZER BOOST/ CUT 18dB, GAIN UP TO 8VOLTS RMS OUTPUT
- SUBWOOFER OUTPUT-LEVEL/ FREQUENCY ADJ. CONTROL
- INPUT SELECT FOR MAIN/ AUX, INDIVIDUAL SENSITIVITY CONTROL
- PRE-AMP VOLUME CONTROL FOR 4 CHANNEL OUTPUT SYSTEMS
- PRE-AMP FADER ADJUSTABLE FOR FRONT/ REAR OUTPUT SYSTEMS
- GOLD-PLATED RCA INPUT CONNECTORS
- ON-BOARD 30V BI-POLAR SWITCHING POWER SUPPLIER, NIGHT ILLUMINATION

SPECIFICATIONS:

5 band Stereo Equalizer: 45Hz, 100Hz, 700Hz, 2KHz, 15KHz, **Boost/ Cut:** 18dB.

Subwoofer Frequency: 30 ~ 120Hz. **Bandwidth:** specific to each band-Hi Shelving.

Frequency Response: 10Hz ~ 50KHz, +/- 1dB, **Input/ Output Impedance:** 10 K Ω / 50K Ω ,

S/N ratio: 105dB/ Ref. 1V Input. **Stereo Separation:** 75dB/ 1KHz.

Input Sensitivity: 50mV ~ 3Volts RMS, **Max. Output:** 8V RMS. **THD:** 0.005%.

Operating Voltage: 11 ~ 15V Negative ground. **Size(H \times W \times D):** 30m/m x 178m/m x 112m/m

<http://www.easoco.com.tw>